ER-2 X-band Doppler Radar (EXRAD) Nadir

Data Description

IMPACTS 2022 Level 1B RevDraft Data Description

Gerald Heymsfield, Lihua Li, Matt McLinden, Peter Pantina, 2022/08/03

EXRAD Level 1B data consist of calibrated radar products (reflectivity, Doppler velocity, spectrum width, normalized radar cross section) with associated time and spatial information. The data products have been processed with a running average, sampled every 0.25 seconds.

Level 1B data is in a nested HDF5 file. Groups are:

- /Information (for general information)
- /Time (for timestamps)
 - o /Data
 - o Information
- /Products (for radar data products)
 - o /Data
 - o /Information
- /Navigation (for radar position and pointing information)
 - o /Data
 - /Information

This RevA data does not use HDF5 attributes, so most data fields have associated data fields describing the information and units. Look in the '/Information' subgroups. For example, the description of radar reflectivity ('/Products/Data/dBZe') is found in /Products/Information/dBZe_description. These 'units' and 'description' fields are not listed in this document.

Please contact Matt L. Walker McLinden (matthew.l.mclinden@nasa.gov) with questions or comments about this data.

Data Field	Units	Dims.	Information		
/Information - General Information					
Aircraft	Text		Aircraft ('NASA ER-2')		
DataContact	Text		Matthew L. Walker McLinden,		
			(`matthew.l.mclinden@nasa.gov')		
ExperimentName	Text		IMPACTS2022		
FlightDate	Text		Flight date		
InstrumentPI	Text		Instrument PI, ('Gerry		
			Heymsfield, NASA/GSFC')		
L1A_ProcessDate	Text		L1A File Process Date		
L1B ProcessDate	Text		L1B File Process Date		
L1B Revision	Text		Revision Letter		
L1B Revision	Text		Describes updates per revision.		
Note					

MissionPI	Text		Mission PI, ('Lynn McMurdie,
M133101111	IEAU		University of Washington')
RadarName	Text		Radar Name
/Time/Data - Tim			
TimeUTC	Seconds	Time	UTC profile time in Unix Epoch
TTIMEOIC	Seconds	TTIIG	format (seconds since 1970).
			Obtained from aircraft NTP. Note
			that there is a profile every
			0.25 seconds, however profiles
			are overlapping. See
			ResolutionHorizontal6dB for
			horizontal resolution.
/Time/Informatio	n - Auxi	liary Ti	
TimeUTC	Seconds	1	Time of 0 UTC, Jan 01, 2020, for
01Jan2020			reference if the user does not
			have an easy Linux time converter
/Products/Data -	Radar P	roduct I	=
dBZe	10*log1	Range,	Equivalent reflectivity factor in
	0	Time	dB with 1-sigma noise threshold
	(mm^6		applied. $ K ^2 = 0.92$. Use
	/m^3)		/Products/Information/MaskCoPol
			or /Products/Information/SNR for
			thresholding other than 1-sigma.
Velocity	m/s	Range,	Doppler velocity with aircraft
uncorrected	, -	Time	motion correction and 1-sigma
		_	noise threshold applied. Positive
			velocity is upward. Use
			/Products/Information/MaskCoPol
			for thresholding other than 1-
			sigma. Possible intrusion of
			horizontal winds into the Doppler
			measurement due to slight off-
			nadir pointing. Check Navigation
			data (roll/pitch) to estimate the
			impact or contact the radar team.
Velocity	m/s	Range,	Doppler velocity with aircraft
corrected		Time	motion, non-uniform beam filling
			(NUBF), and horizontal wind
			intrusion corrections applied.
			Positive velocity is upward. NUBF
			correction is estimated based on
			the local reflectivity gradient.
			HRRR reanalysis winds were
			interpolated to the flight grid,
			converted to along/cross track
			components and scaled by aircraft
			pitch/roll to create an offset.
	L	L	I I I I I I I I I I I I I I I I

		Deve	
SpectrumWidth	m/s	Range,	Doppler velocity spectrum width
		Time	estimate including aircraft
			motion and beamwidth. 1-sigma
			noise threshold applied. Use
			/Products/Information/MaskCoPol
			or /Products/Information/SNR for
			thresholding other than 1-sigma.
sigma0	10*log1	Time	Ocean Normalized Radar Cross
5 - 9110 0	0 (m^2	1 I IIIO	Section. Only valid over ocean.
	/m^2)		beecton: only varia over becan:
/Products/Inform		Radar Pı	coduct Information
AircraftMotion	m/s	Time	Estimated aircraft motion in the
	, -	_	direction of the beam that has
			been subtracted from the Doppler
			estimate.
			estimate.
Antenna	Degrees	1	Antenna 3 dB one-way beamwidth in
Beamwidth	5		degrees.
AntennaSize	meters	1	Antenna Diameter (0.66 meters)
AveragedPulses	#	1	Number of averaged pulses per
in oragear arbee	"	-	profile. Note that profiles are
			not independent, and are
			-
Encourse a constant	Hz	1	overlapping.
Frequency		1	Radar frequency (9.624 GHz)
GateSpacing	meters	1	Range gate spacing (18.737 meters)
HRRR AlongWind	m/s	Range,	HRRR along-track winds,
	, -	Time	interpreted to the flight grid.
HRRR CrossWind	m/s	Range,	HRRR cross-track winds,
_	, -	Time	interpreted to the flight grid.
MaskCoPol	Special	Range,	Co-polarization signal-to-noise
11401100101	Spectar	Time	mask. (Mask >= N) corresponds
	1	T TIUC	-
	1		with (SNR > N-sigma) noise
			thresholding.
NominalAntenna	Text		Nadir
Pointing			
PRI	Text		'200 us / 250 us staggered'.
			Description of the pulse
			repetition interval.
Range	meters	Range	Range in meters from the aircraft
		_	of each range gate.
Resolution	meters	Range	Approximate horizontal resolution
		1 ~	
Horizontal6dB			defined as the -6 dB width of
Horizontal6dB			
Horizontal6dB			spatial weighting as a function
Horizontal6dB			

Decelution	matama	1	Approximate mention, percelution
Resolution	meters	1	Approximate vertical resolution
Vertical6dB			defined as the -6 dB width of the
	5.7 / 5.7	5	range weighting function
SNR	W/W	Range,	Estimated signal-to-noise ratio.
	,	Time	
Velocity_	m/s	Range,	The horizontal wind offset
horizwind_offset		Time	removed from the NUBF-corrected
			Doppler velocity to yield
			horizontal-wind corrected Doppler
			velocity.
Velocity_	m/s	Range,	The NUBF offset removed from the
nubf_offset		Time	uncorrected Doppler velocity to
			yield NUBF-corrected Doppler
			velocity.
Wavelength	m	1	Radar wavelength
/Navigation/Data	ı — Navig	ation Da	
Drift	degrees	Time	Difference between track and
			heading
EastVelocity	m/s	Time	Eastward portion of velocity
Heading	degrees	Time	Aircraft heading in degrees from
			north. 90 degrees is Eastward.
Height	meters	Time	Aircraft height above sea level.
Latitude	degrees	Time	Latitude
Longitude	degrees	Time	Longitude
NominalDistance	meters	Time	Nominal total along-track
			distance calculated by
			integrating instantaneous
			velocity. Used for simple
			plotting.
NorthVelocity	m/s	Time	Northward portion of velocity
Pitch	degrees	Time	Pitch
Roll	degrees	Time	Roll
Track	degrees	Time	Direction of motion in degrees
	5		from north. 90 degrees is
			Eastward motion.
UpVelocity	m/s	Time	Upward velocity.
dxdr	m/m	Time	Data cross-track distance from
		-	aircraft per radar range.
			Positive is in the starboard
			direction.
dydr	m/m	Time	Data along-track distance from
-		-	aircraft per radar range.
			Positive is in the forward
			direction.
dzdr	m/m	Time	Data vertical distance from the
			aircraft per radar range.
			Positive is in upward direction.